

5130 TTV CABIN

Engine

Deutz TCD 3.6 L04 Tier 4i Diesel Engine
4 Cyl/3620cc Turbocharged/Intercooled
Electronically Controlled
Liquid/Oil Cooled
High Pressure Diesel Injection/Common Rail
120 Rated/127 hp Max @ 2300 rpm
Torque 480 Nm @1600 rpm
100% Bio Diesel Compliant
Engine Speed Programming x2
Powercore Air Filter with Dust Ejectors
Side Vertical Exhaust
Fuel Tank 165 litres

Transmission

TTV 2 Range Variable Transmission
3 Modes (AUTO, Manual, PTO)
Eco/Power Dial
Speed Cruise Control
Active Stationary Control
Wet Clutch Powershuttle (Power Zero)
Powershuttle Modulation—5 stage
Speeds From 47metres per hour to 50km/h
50km/h Road Speed @1900 Rpm
Four Wheel Drive (FWD)-Elec/Hyd Engagement
4 Wheel Independent Braking
Front Suspension
Front & Rear Diff Lock 100% Elec/Hyd Engagement
ASM Auto Diff Lock & 4WD Engagement

PTO

Independent Wet Multidisc Clutch
3 Speed PTO 540/540E/1000
Push Button Control in Cab/Fender
Auto PTO
Interchangeable PTO Spline Function

Wheel Equipment & Miscellaneous

Fixed Fully Welded Radial Wheel Equipment
440/65R28 Front 540/65R38 Rear
Dynamic Front Fenders
55 Degree Steering Angle
100 Kg Front Weight Frame
Standard Rear Fenders
Toolbox



Operator Environment

E class Air Conditioned Cab
Mechanical Cabin Suspension
Aeromat Air Seat
Tilt and Telescopic Steering Wheel
Hi Visibility Glass Roof/Rear Wiper
INFOCENTER Digital Display/colour A post
Trainee Seat with Seatbelt
WOLP Lighting System
CD/Radio Player with Quad Speakers
Telescopic Mirrors
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
60 L/min ECO Hyd System (60l @1600 rpm)
Separate 40L/min Steering Pump
SDD Double Displacement Steering System
Power Beyond Supply
3 Sets of Electronic Remotes with Flow Control
Electronic Hitch with Position & Draft Control
Free Flow Return Line
External Raise & Lower on Rear Fenders
Cat 2 Hook Ends with Telescopic Stabilisers
4650 Kg Lift Capacity
12v Electrical Socket and 7 Pin Socket For Implements

Weights & Dimensions

Wheelbase 2440 mm
Length 4270 mm
Total Height 2740mm
Shipping Weight 5400 kg

Power Farming reserves the right to change standard equipment at any time without prior notice

Revised January 2016